

**Safety Data Sheet****Product Name: SUN/STEEL #1410 Charcoal Metallic****4/1/2024****SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** Sun/Steel  
**SYNONYMS:** W/R Alkyd Gloss Enamel  
**PRODUCT CODE:** 1410 Charcoal Metallic  
**MANUFACTURER:** Bert's Paint Inc.  
**ADDRESS:** 2401 S. 12<sup>th</sup> Street  
Phoenix, AZ 85034

**EMERGENCY PHONE:** 602-495-6000  
**FAX PHONE:** 602-523-9675

**CHEMICAL FAMILY:** Paint Waterbase

**PRODUCT USE:** Industrial Coating  
**PREPARED BY:** Michael Thornham

**SECTION 2: HAZARD(S) IDENTIFICATION**

**Hazard Classification:**

**Label Elements:**

**Hazard symbol:**

(Irritant)



**Inhalation:**

May cause irritation to the respiratory system. Breathing vapors may affect the central nervous system. Move to fresh air.

**Ingestion:**

Harmful if swallowed. Do not induce vomiting

**Skin:**

Irritating to skin.

**Eyes:**

May cause irritation, tearing or redness

**This product contains ingredients that may contribute to the following potential chronic health effects:**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Ingredient</b>	<b>Wt %</b>	<b>CAS #</b>
Ammonia	0 – 1	7664-41-7
Ethylene glycol monobutylether	10 – 15	111-76-2
<b>Aluminum large</b>	<b>0 - 3</b>	<b>????</b>

**SECTION 4: FIRST AID MEASURES**

**Ingestion:** Treat symptomatically. Rinse mouth with water. Give one or two glasses of water. Never give anything by mouth to an unconscious person. Only induce vomiting at the instruction of medical personnel. Get medical attention

**Inhalation:** Remove exposed person to fresh air if adverse effects are observed get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Wash with soap and water, if skin irritation occurs, get medical attention.

**Eye Contact:** Wash out immediately with water for up to 10 minutes. If possible remove contact lenses. Get medical attention.

**SECTION 5: FIRE FIGHTING MEASURES**

**General Fire Hazards:** No unusual fire or explosion hazards noted.

**Extinguishing media:** Water spray. Dry chemical or foam. CO<sub>2</sub> may be ineffective on large fires.

**Special protective equipment:** Wear full protective gear including self-containing breathing apparatus operated in a positive pressure mode with full face piece, coat pants, gloves and boots.

**Conditions to Avoid:** Excess heat may cause containers to rupture. Avoid freezing conditions.

**Incompatibility (Materials to Avoid):** Avoid strong alkaline and acids.

**Hazardous Decomposition:** CO, CO<sub>2</sub>, Oxides of Nitrogen

**Hazardous Polymerization:** Will not occur

**SECTION 6: ACCIDENTIAL RELEASE MEASURES****Action to be taken if material is released or spilled:**

Ventilate area. Avoid unnecessary skin contact. Stop and/or contain spill if it can be done safely, avoiding discharge into drains, sewers, or waterways. Collect by absorption, shovel and/or wet mopping. Also wipe, scrape or soak up in/with an inert material and put in a container for disposal. Avoid contact with eyes.

**Waste Disposal Method:**

Dispose of in accordance with Local, State and Federal Regulations.

**Precautions to be taken in Handling and Storing:**

Use with adequate ventilation. Avoid prolonged breathing of vapor. Avoid prolonged or repeated skin contact.

**OTHER PRECAUTIONS:**

Avoid all Sources of Heat.

**SECTION 7: HANDLING AND STORAGE****Precautions for safe handling:**

Observe good industrial hygiene practices. Provide adequate ventilation. Wear appropriate PPE.

Avoid contact with eyes and prolonged or repeated contact with skin. Avoid breathing mists or vapors. When using, do not eat, drink or smoke.

Stir well before use. Keep container closed when not in use.

Minimize contact with air to reduce contamination with mold, fungus, or other organisms which could cause decomposition or spoilage. Wash thoroughly after handling.

**SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION**

**General Information:** Use personal protective equipment as required.

**Respiratory Protection:**

Consult with an industrial hygienist to determine the appropriate respiratory protection for your specific use of this material. A respiratory protection program compliant with all applicable regulation must be followed whenever workplace conditions require the use of a respirator. Use of proper respiratory protection is recommended.

**Ventilation:**

Maintain good ventilation to keep product vapor concentrations below specified limit values.

**Skin Protection:**

Protective Gloves: Suitable gloves should be used to limit effect of skin over-exposure.

**Eye Protection:**

Goggles or face shield are recommended.

**Other Protective Clothing or Equipment:**

To prevent repeated or prolonged skin contact, wear appropriate PPE and boots/shoes.

**Work/Hygienic Practices:**

Eye washes and safety showers in the workplace are recommended, as well as barrier creams, daily showers and a change of clothes.

**SECTION 9: PHYSICAL AND CHEMICAL CHARACTERISTICS**

Boiling Range	212°F (water) 100°C
Solubility in water	Soluble
Flash Point	ND
Solids by weight	27.82 ± .5
Volatile by weight	57.22 ± .5
Specific gravity	1.0396
Weight per gallon	8.66
Coatings VOC	2.99 lbs (359.22 g/L)
Material VOC	1.19 lbs (142.83 g/L)
Appearance	Viscous Liquid
pH	8 - 9
Vapor density	Heavier than air
Odor	mild

**SECTION 10: STABILITY AND REACTIVITY DATA**

**Stability:** material is stable under normal conditions

**Conditions to avoid:** - Do not freeze

**Incompatibility:** (Materials to avoid): Strong oxidizing agents, Alkalis and Bases

**Hazardous Reactions:** Will not occur:

**Hazardous Decomposition:** Thermal decomposition or combustion may generate smoke, carbon monoxide, carbon dioxide, hydrogen chloride, chlorinated compounds, and other products of other incomplete combustion. Irritating and toxic substances may be emitted upon combustion, burning, or decomposition of dry solids.

**SECTION 11: TOXICOLOGICAL INFORMATION****Acute Toxicity:**

Product: No information available.

**Component:**2-butoxyethanol

TWA 20 ppm

PEL 50ppm 240mg/m<sup>3</sup>

Respiratory sensitization: No information available.

Skin sensitization: No information available

**Chronic Effects:**

Carcinogenicity: No information available

Mutagenicity: No information available

Reproductive: No information available

**SECTION 12: ECOLOGICAL INFORMATION****Product:**

No ecological information on this product regarding acute toxicity to fish, aquatic Invertebrates or aquatic plants.

**Component:**Acute toxicity to Fish:

No information available on Aquatic Invertebrates and Aquatic Plants

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Disposal Instructions:**

Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State and local regulations. Empty containers retain product residue, follow label warnings even after container is emptied.

**SECTION 14: TRANSPORTATION INFORMATION**

**DOT** Not regulated

**IMDG** Not regulated

**IATA** Not regulated

**SECTION 15: REGULATORY INFORMATION**

**US Federal Regulations –**

USA Yes, all components are listed or exempt

**SARA 311/312 hazardous categorization**

Hazardous Categories

Acute Health Hazard	No
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of pressure Hazard	No
Reactive Hazard	No

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

2-Butoxyethanol 111-76-2

**SECTION 16: OTHER INFORMATION**

**HMIS Hazard ID:**

Health	2
Flammability	0
Physical Hazards	0

- Rating: 0 Minimal  
 1 Slight  
 2 Moderate  
 3 Serious  
 4 Severe \* chronic health effect

**DISCLAIMER:**  
*The information contained herein has been received from raw material suppliers and other sources and is believed to be reliable. Bert's Paint Inc. makes no warranty expressed or implied, regarding the accuracy of this data or the results to be obtained from the use thereof. Bert's Paint Inc. assumes no responsibility for injury from the use of this product described herein.*