

SUNBURST COATINGS

2401 South 12th Street
Phoenix, AZ 85034
(602) 495-6000

PRODUCT DATA SHEET SUN/STEEL #HP-Dry

DESCRIPTION

Sun/Steel HP-Dry is an additive for Sun/Steel products that will substantially improve dry times to touch and early moisture resistance. HP-Dry will not negatively affect the performance or durability of the Sun/Steel product.

ADVANTAGES

- VOC 0.00 Coating:
- VOC 0.00 Material
- Improves dry to touch times
- Unchanged corrosion resistance
- Improved early moisture resistance
- Reduces with water
- Free of lead and chromate hazards
- No flash point –

Instructions for Use

Addition of HP-Dry is recommend at a level of 6 Fluid ounces per 1 gallon (128 fl oz) of Sun/Steel WR Alkyd paints.

Add HP-Dry to Sun/Steel product and power mix slowly for 2 to 3 minutes before application.

Viscosity may increase slightly, thin with water as needed.

CLEAN-UP

Use water when wet. If no longer water soluble, then clean with Lacquer Thinner. Follow manufacturer's safety recommendations when using any solvent

VOC

COATING VOC: 0.00

This is an "artificial" VOC computation that the EPA and AQMD use to regulate paints and coatings that contain either water or exempt solvents. The *COATING VOC* is sometimes called the *Regulatory VOC*, and this is the VOC that air quality districts use to determine whether or not the paint is in compliance with the limits set by a rule.

MATERIAL VOC: 0.00

This is the *actual or real amount of VOC that a gallon of paint contains*. Always use the MATERIAL VOC to calculate actual VOC emissions.

STORAGE

WINTER:

PROTECT FROM FREEZING:

Store product inside a building, preferably with heat to maintain a climate of no less than 50°F. If stored outside, protect with blanket material and store under canopy if possible.

SUMMER:

PROTECT FROM EXTREME HEAT:

Store inside a building or under canopy to prevent direct sunlight exposure. Extreme heat will destabilize the product by affecting to pH and resins.

Flammability

Non-Flammable emulsion of resins and water

CAUTIONS

DO NOT use this product by itself.

Addition of HP-Dry does not affect the shelf life of Sun/Steel products.

Wash thoroughly after handling product.

Keep container tightly closed and sealed until ready to use. DO NOT transfer contents to a different container without proper labeling.

Thoroughly review product label for safety and cautions prior to using this product. A Safety Data Sheet is available from your local Sunburst Coatings Distributor. Please direct any questions or comments to your local Sunburst Coatings Distributor.

Note: The information, rating, and opinions stated here pertain to the material currently offered and represent the results of tests believed to be reliable.

As of Date: April 3, 2019